



E SEI IN MANI SICURE!

REFLEXX S.r.l.

INFORMATIVE NOTE

rev 00 del 01 marzo 2016

Product: REFLEXX 94 art. R94/S (7)– art. R94/M (8) – art. R94/L (9)- art. R94/ XL (10)

Emessa da G.Isetti – Amm.re Unico

Pag.: 1/3

REUSABLE BICOLORED FLOCKLINED GLOVES TRADEMARK REFLEXX 94

1. NAME AND ADDRESS OF MANUFACTURER:

REFLEXX S.R.L.

Via Passeri, 2

46019 VIADANA (MN)

Tel. 0375 833164 Fax. 0375 464504

2. GENERAL DESCRIPTION OF PRODUCT:

- Latex gloves, five fingers, blue and yellow colored, flocklined with internal soft cotton
- Glove with beaded drip and antiskid surface
- multipurpose glove to protect the hand and / or the product handled. It can be used for general purposes
- Unit Sale in pairs (right hand and left hand) in envelope
- Outer packagings containing No. 50 envelopes (n.5 in packs x 10 pieces)



Imballo		
Cod./Taglie	Confezione	Cartone
R94/S	8032891632741	803289163796
R94/M	8032891632758	8032891637753
R94/L	8032891632765	8032891637760
R94/XL	8032891632772	803289163797

3. QUALITY AND COMPLIANCE WITH REGULATIONS

- As a PPE category III risk according to IT Legislative Decree 475/92 implementing Dir 89/686/EEC (CIMAC, authorized Ministerial: 0465). The product is certified according to the EN 420 , EN 374 part I, II and III and EN 388.



E SEI IN MANI SICURE!

REFLEXX S.r.l.	INFORMATIVE NOTE	rev 00 del 01 marzo 2016
-----------------------	-------------------------	---------------------------------

Product: REFLEXX 94 art. R94/S (7)– art. R94/M (8) – art. R94/L (9)- art. R94/ XL (10)
--

<i>Emessa da G.Isetti – Amm.re Unico</i>	Pag.: 2/3
--	-----------

4. DIMENSIONS AND PERFORMANCE:

Dimensions	Size	Lenght in mm (± 5)	Width in mm. (± 3)	Thickness in mm. (±0,05)
	S / 7	300	95	0.5
	M / 8	300	107	
	L / 9	300	113	
	XL / 10	300	118	

EN 420	construction compliant	in compliance
	measures	in compliance
	donning	in compliance
	dexterity	Maximum dexterity Class 5

EN 374	test water loss	passed
	evidence of air leak	passed

EN 374-3		Performance level of permeation	Breakthrough time (permeation)
	Sulfuric acid 96 %	2	>30'
	Sodium hydroxide 40%	3	>60'
	diethylamine	2	>30'

EN 388		Protection Levels
	Resistance to abrasion	1
	Resistance to blade cut	0
	Resistance to tear	1
	Resistance to perforation	0
	Dexterity	5

Gloves reflexx 94 are controlled according to the sampling method ISO 2859 AQL 1.5 (level G1) for freedom from holes AQL 2.5 (level G1) for more defects and AQL 4.0 (level G1) for minor defects..

For the certification of PPE category III, gloves reflexx 94 are tested with the following chemicals (EN 374): 96% sulfuric acid, sodium hydroxide 40%, diethylamine, and are tested (legislation EN-388) for resistance to abrasion, to cutting by blade, for tearing and perforation.



E SEI IN MANI SICURE!

REFLEXX S.r.l.

INFORMATIVE NOTE

rev 00 del 01 marzo 2016

Product: REFLEXX 94 art. R94/S (7)– art. R94/M (8) – art. R94/L (9)- art. R94/ XL (10)

Emessa da G.Isetti – Amm.re Unico

Pag.: 3/3

5. INSTRUCTIONS FOR USE AND STORAGE:

1. Please read carefully the information note before using the glove.
2. Please keep this information note for the duration of the useful life of the glove.
3. The glove is a device subject to wear and tear so it is recommended the frequent replacement , and in all cases where visually you can see imperfections. Always wear gloves your hands are dry and clean.
4. Do not use gloves when there is a risk of getting caught in the moving parts of machines.
5. The product contains latex rubber. It may cause allergic reactions of type I hypersensitivity and delayed hypersensitivity type IV.
6. Avoid contact with aggressive substances such as fats , oils , acids, hydrocarbons and other chemical agents.
7. Before using the product, test it in real conditions of use.
8. Keep the packaging for further information and to ensure traceability.
9. Keep the product in its original packaging in a dry place at a temperature not exceeding 40°C or below -10 °C.
10. Avoid exposure to sunlight and heat sources.

REFLEXX Srl
Via Passeri, 2 - 46019 VIADANA (MN)
P.I. e C.F. 02085450209
Tel. 0375.833164 - Fax 0375.464504
e-mail: info@reflexx.com